




Get the water you want with Watts® drinking water systems with Kwik-Change™ cartridges

Many water quality problems.



Contaminants



Water for drinking, beverages and preparing foods should be safe and free from harmful contaminants. This is particularly important if you get your water from a private well. And even if your municipal water meets all standards, it may contain other impurities that could be responsible for long term health effects.

Foul taste & odors

From its passage from clouds to your tap, water comes in contact with many different impurities which can produce foul taste and odors that can ruin the enjoyment of prepared foods and beverages.



Turbidity & color

Cloudy water is due to turbidity, or finely divided particles. Color in water is most often due to dissolved organic matter. These problems result in water that is unpleasant to drink. Turbidity and color in water can easily be corrected with point-of-use water treatment systems.

If you think bottled water is the answer, Think again!

Many individuals are buying bottled water because they are concerned about drinking water quality. Bottled water is expensive, and it's very inconvenient. Water produced by RO systems cost pennies a gallon, compared to a dollar or more for bottled water.



One solution!

Reverse osmosis . . .

Reverse osmosis is recognized by experts as the best technology available to remove the widest spectrum of contaminants, which may be found in drinking water.

Likewise, Watts[®] reverse osmosis systems with Kwik-Change[™] cartridges are considered the *best* drinking water systems available because they are easy to maintain and consistently provide the highest quality water possible!

It' so easy!

Watts® drinking water systems with Kwik-Change™ cartridges are the best choice for busy consumers because they are so easy to maintain.

Cartridges connect to (and disconnect from) the unit by a simple 1/4 turn. It's so easy!



No fuss, no mess!

Unlike conventional units (shown above), filter housings are not required when using Kwik-Change cartridges.

For this reason, there's no need to shut down the system to remove filter housings, simply to change cartridges or membranes.

Features and benefits


- Cartridges connect directly to the unit by a simple 1/4 turn.
- Filter housings are eliminated. No mess during cartridge replacement!
- Internal valves shut-off flow when cartridges are removed.
- Cartridges have double o-rings so they won't leak.
- Compact design, so the unit requires less space below your sink!
- All components are an integral part of the unit, which requires fewer tube connections for greater reliability.
- Back-flow prevention valves are installed between the elements, for water quality assurance.



Two tank options

Metal or our highly p

Metal or our highly popular RO-PRO® plastic storage tanks are available.



Designer faucets

All systems come with our unique top mount designer faucets. (Installation is completed from above the counter top.)

Models (with 3/8" tubing to tank and to faucet)

Model Number	Capacity* (Gals. / day)	Tank
WQC4RO11-50PT	50	Plastic
WQC4RO11-50MT	50	Metal
WQC4RO13-100PT	100	Plastic
WQC4RO13-100MT	100	Metal

Specifications

Typical rejection rate*	98% (total dissolved solids)
Operating pressure	35 to 100 psi
Cartridge replacement	6 to 12 months based on usage
Membrane replacement	2 years**
Dimensions (unit)	12" x 12" x 3" and 13" x 12" x 3"

^{*}Based on 60 psi and 77°F. **Based on water quality and use.

Replacement elements

Model (GPD)	Sediment	Carbon Block (Pre Filter)	RO Membrane	Carbon GAC (Post Filter)
50	WQCSC11	WQCCC11	WQCM11-50	WQCGAC11
100	WQCSC13	WQCCC13	WQCM13-100	WQCGAC13

Watts® filter units with Kwik-Change™ cartridges

We now offer a complete line of filter systems with Kwik-Change™ cartridges, including cartridges for taste, odors and chlorine reduction; sediment; hollow fiber membrane for ultra filtration; and cartridges with antibacterial activated carbon.

Filter units (with 10" cartridges, bracket and boxed)

Model Number	Stage	Sediment	Carbon	Hollow Fiber Membrane	Flow Rate (GPM)
WQCFU-AC	1		Х		0.5
WQCFU-S	1	X			0.5
WQCFU-D	2	X	X		0.5
WQCFU-T	3	X	X	X	0.5

Note: Models listed above use 10" cartridges. Operating temperature: 40° F to 100°F.



Watts® filtration system with Kwik-Change™ cartridges.

Replacement cartridges and components

Cartridge type	Part Number			Micron	Capacity (gallons)		
	10"	11"	13"		10"	11"	13"
Activated carbon	WQCCC10	WQCCC11	WQCCC13	5	1,500	2,000	2,500
Sediment	WQCSC10	WQCSC11	WQCSC13	5	900	1,000	1,100
Hollow fiber membrane	WQCHFC10	WQCHFC11	WQCHFC13	0.1-0.3	1,500	2,000	2,500
Antibacterial carbon	WQCABC10	WQCABC11	WQCABC13	5	1,500	2,000	2,500

Note: Brackets for filter units are fixed and can accommodate 10", 11" and 13" cartridges. Capacity based on water quality and use.

Limited warranty: Watts® reverse osmosis systems and filter units with Kwik-Change cartridges come with a one year limited warranty covering defects in material and workmanship, extended to the original purchaser for one year from date of installation. See warranty card for more details.

Available from authorized dealers

Watts reverse osmosis and drinking water systems are available from independent dealers who are trained to install and service our equipment. For sales, installation and service, please contact the dealer listed below.



